

DUAL VOLTAGE MODULES

PAR36DV - 11 Flash Patterns (Wide Angle Optics)



- Multiple units can be linked for synchronised / alternate flash
- Waterproof with sealed for life electronics
- EMC approved
- 24 month warranty.

Specifications:

- Lens: Polycarbonate
- Body: Aluminium coated black
- Current draw: 12V - 750mA (max)
- Weight: 0.24Kg
- Dimensions: 136 (d) x 26mm (d).

Part No	Voltage	Colour
PAR36DVA	12/24V	Yellow
PAR36DVR	12/24V	Red
PAR36DVB	12/24V	Blue

XLED6DV - 11 Flash Patterns (Wide Angle Optics)



- Xtreme LED Light
- Multiple units can be linked for synchronised / alternate flash
- Waterproof with sealed for life electronics
- EMC approved
- 24 month warranty.

Specifications:

- Lens: Polycarbonate
- Body: Aluminium coated black
- Weight: 0.24Kg
- Current draw: 12V - 700mA
- Dimensions: 148 (l) x 55 (d) x 30mm (h).

Part No	Voltage	Colour
XLED6DVA	12/24V	Yellow
XLED6DVR	12/24V	Red
XLED6DVB	12/24V	Blue

R65 MODULES

Our new range of modules are available with 3, 4 and 6 LEDs and are designed for applications where ECE R65 Approved auxiliary warning lights are required.



Main Features:

- 6 Flash Patterns
- 3 ECE R65 Approved Flash Patterns (Single Flash, Double Flash & Quad Flash)
- IP67 rated ingress protection
- Multiple Units can be linked for synchronised / alternate flash
- EMC Approved (ECE R10).

Materials:

- Lens: Polycarbonate
- Base: Aluminium.

Warranty:

- 24 month warranty.



LED3R65

- Weight: 0.07kg
- Current Draw: 12V - 400mA
- Dimensions: 89 (w) x 34 (d) x 22mm (h).



LED4R65

- Weight: 0.09kg
- Current Draw: 12V - 600mA
- Dimensions: 117 (w) x 34 (d) x 22mm (h).



LED6R65

- Weight: 0.12kg
- Current Draw: 12V - 850mA
- Dimensions: 155 (w) x 34 (d) x 22mm (h).

Part No	Voltage	Colour
3 LED MODULES		
LED3R65A	12/24V	Yellow
LED3R65B	12/24V	Blue
LED3R65R	12/24V	Red
4 LED MODULES		
LED4R65A	12/24V	Yellow
LED4R65B	12/24V	Blue
LED4R65R	12/24V	Red
6 LED MODULES		
LED6R65A	12/24V	Yellow
LED6R65B	12/24V	Blue
LED6R65R	12/24V	Red