

FEATURES

- High Resolution 5" Digital TFT LCD
- Free Input voltage (DC 10V ~ 30V)
- LED Backlight technology (250cd/m2)
- Capacitive Touch Key
- Shutter camera support
- 2 Camera Inputs
- 2 Trigger Inputs
- Tamperproof function
- Anti Reflection Window
- Automatic Brightness Control
- Auto Scan function
- Auto Power ON/OFF
- NTSC/PAL Auto Switch
- Multi-lingual OSD control
- Built-in Speaker
- Electronic Distance Marker (Parking line)
- Bracket rails and Heavy Duty mounting possibility
- Speedswitch function via tacho signal
(in case of frontview purpose)
- Sunvisor – included



Specifications

Power input	10V~30V DC	
Video System	NTSC, PAL signal Compatible	
Panel	5" Digital	
Resolution	640(H) X 480(V) X RGB	
Format	4:3	
Brightness	250cd/m2	
Contrast Ratio	500:1	
Display Mode	Single	
Speaker	8 ohm/0.3Watt	
Viewing Angle	Top: 50°, Bottom: 70°, Left: 70°, Right: 70°	
Operating Temperature	-35°C ~ 80°C	
Dimensions	148(W) X 104(D) X 29(H)mm	
Weight	Approx. 500g	
Accessories	<ul style="list-style-type: none"> - Bracket (Rail Type) - Screw kit 	<ul style="list-style-type: none"> - Sunvisor - Instruction manual