



SENSORS: Temperature sensors and switches

MOTOMETER

powered by solutions

The following temperature sensors are available

- Temperature sensor (40 °C – 120 °C)
- Temperature sensor (50 °C – 150 °C)
- Temperature sensor with warning contact (40 °C – 120 °C)
- Temperature switch

Temperature sensor

MOTOMETER temperature sensors have a NTC resistor, that records the temperature of oil, water or air and forwards the measurement result to a temperature display. Brass casings are used, along with a special gel in the sensor housing, for the fast transfer of the detected temperature with little loss.

Operation is possible with 12 Volt or 24 Volt on-board supply system. The temperature range is between 40 °C and 120 °C or between 50°C and 150°C, depending on the type.

In addition to the listed standard temperature sensors, we can also offer you customised solutions.

MOTOMETER GmbH

Talweg 8 | 75417 Muehlacker-Lomersheim/DE

Phone +49 7041 9695-0 | Fax +49 7041 9695-55 | E-Mail info@motometer.de

www.motometer.de



SENSORS: Temperature sensors and switches



Temperature sensors (40 °C – 120 °C)

The resistance characteristic is identical for all sensors

60 °C	134 Ohm
90 °C	51.2 Ohm
100 °C	38.5 Ohm

Compatible with MOTOMETER temperature displays

641.011 xxxx
641.012 xxxx

The sensors are also available unearthed.

Thread	Measuring range	Voltage	Length	Connection	Part No.
M10 x 1 K	40 – 120 °C	6 – 24 Volt	29 mm	A 6,3 x 0,8	642.007.1015
M14 x 1.5	40 – 120 °C	6 – 24 Volt	21 mm	Round connector 4 mm	642.007.1018
M14 x 1.5	40 – 120 °C	6 – 24 Volt	29 mm	Thread M 4	642.007.1001
M14 x 1.5	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1006
M14 x 1.5	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8 unearthed	642.011.1001
M16 x 1.5	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1021
M18 x 1.5	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1008
1/8"-27 NPTF	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1014
5/8"-UNF-3A	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1012
5/8"-18UNF-2A	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8 unearthed	642.011.1007
1/4"-18 NPTF	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1010
1/2"-14 NPTF	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1009
1/2"-14 NPTF	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8 unearthed	642.011.1004
R 3/8"	40 – 120 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	642.007.1013

MOTOMETER GmbH

Talweg 8 | 75417 Muehlacker-Lomersheim/DE

Phone +49 7041 9695-0 | Fax +49 7041 9695-55 | E-Mail info@motometer.de

www.motometer.de



SENSORS: Temperature sensors and switches



Temperature sensor (50 °C – 150 °C)

The resistance characteristic is identical for all sensors

60 °C 221.2 Ohm

90 °C 83.0 Ohm

120 °C 36.5 Ohm

Compatible with MOTOMETER temperature displays

641.011 xxxx

641.012 xxxx

Thread	Measuring range	Voltage	Length	Connection	Connection characteristic	Part No.
M10 x 1k	50 – 150 °C	6 – 24 Volt	16 mm	T-connector A 6,3 x 0,8	straight	642.009.1026
M12 x 1.5	50 – 150 °C	6 – 24 Volt	30 mm	A 6.3 x 0.8	angled	642.009.1001
M14 x 1.5	50 – 150 °C	6 – 24 Volt	15 mm	A 6.3 x 0.8	straight	642.009.1002
M14 x 1.5	50 – 150 °C	6 – 24 Volt	30 mm	A 6.3 x 0.8	straight	642.009.1021
M22 x 1.5	50 – 150 °C	6 – 24 Volt	30 mm	A 6.3 x 0.8	straight	642.009.1004
1/8"-27 NPTF	50 – 150 °C	6 – 24 Volt	30 mm	A 6.3 x 0.8	straight	642.009.1020
3/8"-18 NPTF	50 – 150 °C	6 – 24 Volt	29 mm	A 6.3 x 0.8	straight	642.009.1034
1/2"-14 NPTF	50 – 150 °C	6 – 24 Volt	30 mm	A 6.3 x 0.8	straight	642.009.1019

MOTOMETER GmbH

Talweg 8 | 75417 Muehlacker-Lomersheim/DE

Phone +49 7041 9695-0 | Fax +49 7041 9695-55 | E-Mail info@motometer.de

www.motometer.de



SENSORS: Temperature sensors and switches



Temperature sensor with warning contact (40 – 120 °C)

Temperature sensors with a warning contact are used in vehicles and machines to record the temperature of oil, water or air and to forward the measurement result to a temperature display. A warning contact is closed at the same time as a defined temperature is reached.

MOTOMETER temperature sensors with a warning contact have a NTC resistor, a brass casing and a special gel for rapid temperature transfer with little loss.

The pre-tensioned bimetal strips are relaxed when the defined temperature is reached.

Operation is possible with 12 Volt or 24 Volt on-board supply system. The temperature range is between 40 °C and 120 °C, and the switching contact is in the range 80 °C to 118 °C. The switching capacity is 3 W.

The version is grounded.

The resistance characteristic is identical for all sensors

60 °C 134 Ohm
90 °C 51.2 Ohm
100 °C 38.5 Ohm

Compatible with MOTOMETER temperature displays

641.011 xxxx
641.012 xxxx

In addition to the listed standard temperature sensors with warning contact, we can also offer you customised solutions.

MOTOMETER GmbH

Talweg 8 | 75417 Muehlacker-Lomersheim/DE

Phone +49 7041 9695-0 | Fax +49 7041 9695-55 | E-Mail info@motometer.de

www.motometer.de



SENSORS: Temperature sensors and switches



Warning contact (+/- 3 °C)	Thread	Measuring range	Connection	Part No.
80 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1001
90 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1002
92 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1003
94 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1004
95 °C	1/2"-14 NPTF	40 – 120 °C	A 6.3 / A 4.8	642.016.1015
96 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1005
98 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1006
100 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1007
100 °C	M14 x 1.5	40 – 120 °C	A 6.3 (T-Form)	642.016.1022
103 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1008
103 °C	M18 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1025
103 °C	1/2"-14 NPTF	40 – 120 °C	A 6.3 / A 4.8	642.016.1016
106 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1009
110 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1010
115 °C	M14 x 1.5	40 – 120 °C	A 6.3 / A 4.8	642.016.1012
120 °C	M14 x 1.5	50 – 150 °C	A 6.3 / A 4.8	642.040.1001
130 °C	M14 x 1.5	50 – 150 °C	A 6.3 / A 4.8	642.018.1001

MOTOMETER GmbH

Talweg 8 | 75417 Muehlacker-Lomersheim/DE

Phone +49 7041 9695-0 | Fax +49 7041 9695-55 | E-Mail info@motometer.de

www.motometer.de



SENSORS: Temperature sensors and switches



Temperature switch

Temperature switches are used in vehicles and machines to record the temperature of oil, water or air and to close a warning contact when a defined temperature is reached.

The MOTOMETER temperature switches have pre-tensioned bimetal strips. The use of brass casings and a special integrated gel allows fast temperature transmission with little loss. When the respective temperature range is reached, the pre-tensioning is released and the contact is closed with a switching capacity of 3 W or 100 W.

Operation is possible with an onboard 12 Volt or 24 Volt mains. The switching contact closes slowly at temperatures of 35 °C to 220 °C.

MOTOMETER temperature switches are also available mass-free.

In addition to the listed standard temperature switches, we can also offer you customised solutions.

Warning contact	Thread	Voltage	Tolerance	Switching capacity	Connection	Characteristic	Part No.
35 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1030
55 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1005
60 °C	M14 x 1.5 k	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8	conical thread	610.003.1043
70 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1007
80 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8	short conical thread	610.003.1023
85 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1008
90 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1009
92 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1010
95 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1012
95 °C	1/2"-14 NPTF	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1027

MOTOMETER GmbH

Talweg 8 | 75417 Muehlacker-Lomersheim/DE

Phone +49 7041 9695-0 | Fax +49 7041 9695-55 | E-Mail info@motometer.de

www.motometer.de



SENSORS: Temperature sensors and switches



Warning contact	Thread	Voltage	Tolerance	Switching capacity	Connection	Characteristic	Part No.
96 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8	unearthed	610.003.1031
97 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1013
100 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8	short conical thread	610.003.1025
103 °C	1/2"-14 NPTF	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1045
105 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1014
105 °C	1/2"-14 NPTF	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1028
110 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1015
115 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1016
120 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1017
130 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	3 W	A 6.3 x 0.8		610.003.1019
150 °C	M10 x 1.5	6 – 24 Volt	+/- 5 °C	3 W	M 4		610.010.1004
170 °C	M10 x 1.5	6 – 24 Volt	+/- 5 °C	3 W	M 4		610.010.1001
55 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	100 W	A 6.3 x 0.8	unearthed	610.006.1006
On:70 °C	M14 x 1.5	6 – 24 Volt	Off:60 °C	100 W	A 6.3 x 0.8	control switch unearthed	610.004.1006
On:82 °C	M18 x 1.5	6 – 24 Volt	Off:74 °C	100 W	A 6.3 x 0.8	control switch unearthed	610.004.1004
On:86 °C	M18 x 1.5	6 – 24 Volt	Off:81 °C	100 W	A 6.3 x 0.8	control switch unearthed	610.004.1003
On:92 °C	M18 x 1.5	6 – 24 Volt	Off:85 °C	100 W	A 6.3 x 0.8	control switch unearthed	610.004.1007
On:86 °C	M22 x 1.5	6 – 24 Volt	Off:81 °C	100 W	A 6.3 x 0.8	control switch unearthed	610.004.1010
On:92 °C	M22 x 1.5	6 – 24 Volt	Off:85 °C	100 W	A 6.3 x 0.8	control switch unearthed	610.004.1005
100 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	100 W	A 6.3 x 0.8	unearthed	610.006.1002
110 °C	M14 x 1.5	6 – 24 Volt	+/- 3 °C	100 W	A 6.3 x 0.8	unearthed	610.006.1003
Double Temperature switch							
On:70 °C	M22 x 1,5	12 Volt	Off:80 °C	9,6 W	3-pin Minitimeter	unearthed	610.006.1011
On:70 °C	M22 x 1,5	12 Volt	Off:60 °C	9,6 W	3-pin Minitimeter	unearthed	610.006.1011

All data subject to technical changes.

MOTOMETER GmbH

Talweg 8 | 75417 Muehlacker-Lomersheim/DE

Phone +49 7041 9695-0 | Fax +49 7041 9695-55 | E-Mail info@motometer.de

www.motometer.de