

XENON BEACONS (XNB RANGE)

High brightness Xenon Beacon range, which can be either single or double flash. Fitted with internal fresnel lens and easy clean outer lens cover.



Main Features:

- 7 Watt
- EMC approved (ECE R10)
- Dual Voltage 12/24V
- Vibration protected circuits
- Reverse polarity protection
- Built-in option of either single or double flash
- 70 mph rated on magnetic versions
- Meets IP56 international protection standards
- -30°C to +50°C extreme temperature reliability.



Source: Ford Europe

Materials:

- High performance ABS base
- Non-fading acrylic or polycarbonate lens.

Replacement Parts:

- Lens.

Warranty:

- LAP offer a 12 month or 2000 hour guarantee on our products, subject to the item being fitted and used in accordance with the correct instructions.

Colours



Applications



Part No	Voltage	Action	Colours	Current Consumption 12/24V	Flash Rate (Per min)	Mounting	Weight KG (Approx.)
XNB 020	10-30V	Sgl./DbI.FI.	A/B/R/G	1.6/0.8A	125	Magnetic	1.4
XNB 030	10-30V	Sgl./DbI.FI.	A/B/R/G	1.6/0.8A	125	DIN	0.9
XNB 040	10-30V	Sgl./DbI.FI.	A/B/R/G	1.6/0.8A	125	Flexi DIN	1.0
XNB 050	10-30V	Sgl./DbI.FI.	A/B/R/G	1.6/0.8A	125	Three Point	0.8
XNB 060	10-30V	Sgl./DbI.FI.	A/B/R/G	1.6/0.8A	125	Single Point	0.85